









RPX 35 REVERSIBLE PLATE COMPACTORS





FEATURES & BENEFITS

- Robust design for long-life and use in the harshest site conditions.
- Electric start with key ignition & LED warning lamps, eliminates need for operator training with manual starting.
- Integrated Wheel Kit, ready for safe and easy transporation.
- Control Handle & Additional Fixed Handle with strong locking:-
 - More positive handling & control.

 - Reduces shock loading on control handles.Better fulcrum for pulling machine onto its wheels.
 - Safe for operator moving without relying on moving control handles.
 - No damage to the forward/reverse mechanism.
- Angled baseplate for excellent gradability and travel speeds.
- Low HAV handle, safe for operators to use for long periods.
- High Compaction force for fast work and deep compaction.
- Handle mounted throttle, perfect for the operator
- Compact, high performace, sealed for life Lithium Ion battery. Dry battery = no liquid acid
- Specifically designed for hire and rental markets.
- Paving Pad option available.

TECHNICAL SPECIFICATIONS

Model		RPX 35/40DE Hatz 1B20	RPX 35/50DE Hatz 1B20
Part No.		161.9.201	161.9.204
Width	(mm)	400	500
Storage Length	(mm)	809	809
Operating Length	(mm)	1205	1205
Storage Height	(mm)	1264	1264
Operating Height	(mm)	1067	1067
Plate Size	(mm)	400 x 700	500 x 700
Engine Power	(Hp / kW)	4.2 / 3.1	4.2 / 3.1
Engine RPM		3000	3000
Static Pressure	(kg/m^2)	1661	1350
Centrifugal Force	(kN)	35	35
Frequency	(Hz)	95	85
Max Gradient	(°)	20	20
Max. Travel Speed	(m/min)	27	26
Weight Class	(kg)	160	200
Weight	(kg)	189	194
Noise Level	(dB(A))	108	108



INTEGRATED WHEEL KIT & FOOT STAND FOR EASY TRANSPORTATION



FIXED HANDLE TO AID TRANSPORTATION



ELECTRIC, KEY IGNITION START & LED WARNING LAMPS



HANDLE MOUNTED THROTTLE **LEVER**

